



## SnapCenter repository HA reports unhealthy replication status

[https://kb-stage.netapp.com/data-mgmt/SnapCenter/SC\\_KBs/SnapCenter\\_repository\\_HA\\_reports\\_unh...](https://kb-stage.netapp.com/data-mgmt/SnapCenter/SC_KBs/SnapCenter_repository_HA_reports_unh...)

Updated: Wed, 22 Apr 2026 01:47:30 GMT

### Applies to

- SnapCenter Server (SC)
- SnapCenter High Availability (HA)

### Issue

- SnapCenter `Get-SmRepositoryConfig` reports an unhealthy replication status with error-

```
Replication status: UnHealthy
```

```
Replication issues: Replication of the repository failed with error:  
Replication of the repository failed with error: Worker 1 failed executing  
transaction 'ANONYMOUS' at source log mysql-bin, end_log_pos; Could not execute
```

Update\_rows event on table nsm.nsm\_job\_message; Can't find record in 'nsm\_job\_message', Error\_code: 1032; handler error HA\_ERR\_KEY\_NOT\_FOUND; the event's source log mysql-bin.000011, end\_log\_pos. You can manually correct the error or rebuild the repository on 0.0.0.0 by running the 'Set-SmRepositoryConfig' cmdlet with the '-ServerToRebuild' option.. You can manually correct the error or rebuild the repository on 0.0.0.0 by running the 'Set-SmRepositoryConfig' cmdlet with the '-ServerToRebuild' option.

- An attempt to rebuild the replication using Set-SmRepositoryConfig fails with the same error.